


Introduction to Parallelism

Daniel Lawson — University of Bristol

Lecture 09.1 (v4.0.0)


Working in Parallel



Questions

- ▶ When can an **algorithm** be run in parallel, i.e. concurrently?
- ▶ Which **parts** of an algorithm can be sped up?
- ▶ What **scale** of parallelism are possible?
 - ▶ ... within a processor?
 - ▶ ... across components on a single computer?
 - ▶ ... across machines within an institution?
 - ▶ ... distributed across time and space?

CPUs are parallel processing units



- ▶ Each CPU (central processing unit) is a sophisticated architecture.
- ▶ Parallelism exists in:
 - ▶ how the CPU accesses memory,
 - ▶ how memory is structured (L1 cache, general memory),
 - ▶ how the CPU processes registers. . .
- ▶ You only need to write **vectorized code** in order to access this.

Computers are parallel processing units

- ▶ General purpose parallelism can be:
- ▶ A single machine containing a **multi-core CPU** (central processing unit):
 - ▶ Most commonly coded with OpenMP,
 - ▶ The cores share memory and are multipurpose, and hence coding is easy,
 - ▶ Accessed via simple libraries.
- ▶ A **GPU** (graphical processing unit):
 - ▶ Most commonly accessed via **libraries**, e.g. OpenCL, PyTorch, etc.
 - ▶ Contain a large number of relatively limited cores that can perform simple computations (e.g. matrix operations; linear computations) efficiently,
 - ▶ Dedicated GPU hardware is multipurpose (e.g. TPU), i.e. has an increased feature set.

Clusters of computers are parallel processing units

- ▶ **Multiple machines** act as a processing unit, either:
 - ▶ A set of (identical) machines on a high-bandwidth network connection, able to perform **computation as a coherent unit**.
 - ▶ Extremely flexible and the most popular setup; a “supercomputer”.
 - ▶ Coded with Hadoop, Spark, OpenMPI, etc depending on goal.
- ▶ **Massively distributed computing**, able to communicate but not rely on one another.
 - ▶ Non-realtime computations can be distributed and returned when ready.
 - ▶ For example, **SETI@Home**; **Folding@Home**, internet routing; low priority access to Amazon AWS/Azure.
 - ▶ Biological decision making (the brain),
 - ▶ Societal decision making (social insects, humans).

Formal classes of parallel computer

- ▶ Computer scientists may think in terms of **control** (instruction sets) and **processing** (data streams):
- ▶ Single Instruction stream, Single Data stream (**SISD**):
 - ▶ Single control, single processor. A sequential processor, as we conceptualise a computer.
- ▶ Single Instruction stream, Multiple Data stream (**SIMD**):
 - ▶ Single control, multiple processors. dedicated to *vector calculations*.
- ▶ Multiple Instruction stream, Single Data stream (**MISD**):
 - ▶ Used for streaming computations (e.g. *splitting pipes*) for fast response, e.g. the space shuttle. . .
- ▶ Multiple Instruction stream, Multiple Data stream (**MIMD**):
 - ▶ Multiple control, multiple processors.
- ▶ They also think in terms of shared vs distributed (interconnected) memory.
 - ▶ e.g. MIMD **may** have distributed memory.

Parallel algorithms for data science

- ▶ Most parallel coding is about thinking about your problem:
 - ▶ What **dependencies** (on the output of some other computation) really exist?
 - ▶ How can you write code avoiding **unnecessary dependencies**?
- ▶ There are hardcore parallel algorithms and paradigms. We just need to know:
 - ▶ Should we try to parallelise to solve a particular problem?
 - ▶ Will simple tricks work for you?
- ▶ This involves describing your problem in a well-supported paradigm

Embarrassingly parallel algorithms

- ▶ The meaning of the word is as in:

"an embarrassment of riches..."

- ▶ **embarrassingly parallel** algorithms are the most important class.
 - ▶ In these, there is **no dependency** between threads.
 - ▶ You can run them in an arbitrary order, in series if needed.
- ▶ Most parallel coding is about turning a problem into a series of embarrassingly parallel algorithms.
 - ▶ Vectorisation is the first

Embarrassingly parallel examples

- ▶ **Monte-Carlo sampling** (for integration or search):
 - ▶ Run a large number of independent, randomised processes.
- ▶ **Grid search** or **Latin hypercube sampling**:
 - ▶ Run a large and (pre-defined or algorithmically defined) set of independent processes.
- ▶ Independent **database queries** (assuming database storage is distributed with compute)
- ▶ **Rendering** of graphics in games/video editing
- ▶ **Note**:
 - ▶ Still not trivial to implement if **memory** or **communication** bandwidth becomes limiting.

Vectorisation

- ▶ Vectorised code is parallelised code.
 - ▶ Each operation for vectorised code is computable independently
 - ▶ The **same** operation is applied to each element (with different data)
 - ▶ **CPU optimisation** is possible and may be straightforward
 - ▶ GPU acceleration is possible
 - ▶ Vectorisations are always **one dimensional** representations
- ▶ A set of standardized elementwise computations is possible:
 - ▶ addition, subtraction, multiplication, division
 - ▶ other operations are possible, this becomes architecture dependent

Vectorisation of K-dimensional objects

- ▶ Matrices can be represented by standardized vectorisation procedures
 - ▶ $A = \begin{bmatrix} a & b & c \\ d & e & f \end{bmatrix}$
 - ▶ **Row major** order: $\text{vec}(A) = (a, b, c, d, e, f)$
 - ▶ **Column major** order: $\text{vec}(A) = (a, d, b, e, c, f)$
- ▶ Matrix multiplication:
 - ▶ Is just sums of the correct components of the vectorised matrices
 - ▶ Choice of row vs column major order affects efficiency!
- ▶ Parallelization:
 - ▶ On a **shared memory** machine, the computations are distributed
 - ▶ Otherwise a **memory distribution** problem
- ▶ Efficient implementations for many common computations

Vectorisation and time complexity

- ▶ Assuming no parallelization:
- ▶ A **for loop** with N iterations is $O(N)$
- ▶ A **vectorisation** with N elements is $O(N)$
- ▶ But the vectorised code may still be orders of magnitude faster:
 - ▶ It often can be pushed into low-level code (C backend)
 - ▶ It can exploit CPU memory architecture: **caching** the correct content to avoid overhead
 - ▶ It can exploit CPU compute architecture: **multiple registers** in parallel
- ▶ Vectorisation also leads directly into parallel implementations:
 - ▶ It emphasises dependencies,
 - ▶ It encourages reordering of loops which can reduce time complexity.

Portfolio 09.1.1 - Vectorisation in pytorch

- ▶ Neural networks are usually expressed almost entirely as tensor operations (matrix products, convolutions, element-wise functions). Why has modern machine learning converged on this representation?
 - ▶ Explain how automatic differentiation makes this possible.
 - ▶ Can non-neural network models be learned the same way?
What are the limits?

References

- ▶ A Brief Overview of Parallel Algorithms
- ▶ Parallel computing concepts e.g. Amdahl's Law for the overall speedup
- ▶ MISD/MIMD/SIMD/SISD
- ▶ Parallel time complexity