

Mapping, Reducing, and Computational Graphs

Daniel Lawson — University of Bristol

Lecture 09.2 (v4.0.0)


How to write your lines faster

```
FOR (I IN 1:100) {  
  PRINT("I WILL NOT USE LOOPS IN R")  
}
```



Computation Graph

- ▶ How is the computation structured?
- ▶ Which parts are parallisable?
- ▶ Where is the output of one computation required?
- ▶ In this illustration,
 - ▶ Gather Input
 - ▶ Do something in parallel
 - ▶ Collect the answer
 - ▶ Do something else in parallel
 - ▶ Collect the answer
 - ▶ Return
- ▶ There are always sequential limits in e.g. memory allocation, variable construction, etc.



Computation dependence

- **Real example:**

Dimensionality reduced
similarity

procedure EXAMPLE($x[]$, n , m)

while $i \leq n$ **do**

$y[i] \leftarrow f(x[i]; m)$

end while

while $i \leq n$, $j \leq n$ **do**

$z[i, j] \leftarrow g(y[i], y[j]; k)$

end while

return z

end procedure

- Consider a matrix x of dimension n items with m features **and** p CPUs.

- First: compute

$y_i = f(x_i)$, a vector of length $k \ll m$

- Second: compute a similarity

$$z_{ij} = g(y_i, y_j) \approx g'(x_i, x_j)$$

- Raw cost:

$$\Theta(nm + n^2k)$$

- Parallel cost:

$$\Theta(\lceil n/p \rceil m + \lceil n^2/p \rceil k)$$

Parallel speedup

- ▶ There are two key concepts:
- ▶ Total **Speedup** $S_t := \frac{\text{Sequential algorithm runtime}}{\text{Parallel algorithm runtime}} = T_s/T_p$.
 - ▶ The speed benefit of running compute in parallel
 - ▶ $S_t = t/p$ in the best case (for total time t and p processors)
- ▶ **Work efficiency** $E := \frac{\text{Total Sequential compute}}{\text{Total Parallel compute}}$.
 - ▶ The efficiency penalty for running in parallel
 - ▶ $E = 1$ in the best case.
- ▶ For example:
 - ▶ If the runtime t decreased as $t = \Theta(\log(n)/p)$,
 - ▶ and we used $p = \sqrt{n}$ processors,
 - ▶ then the speedup is $\sqrt{n}/\log(n)$ whilst the efficiency is $1/\log(n)$.
 - ▶ These can be defined both for actual times, and rates.

Maximum speedup

- ▶ **Amdahl's Law**: Max speedup = $\frac{1}{(1-P)+P/S_p}$
 - ▶ where P is the **parallelisable proportion** of the algorithm
 - ▶ and S_p is the **Speedup** for the parallelisable proportion
 - ▶ This follows directly from writing the compute time of the parallel algorithm:

$$T_t = (1 - P)T_s + PT_s/S_p$$

- ▶ it asymptotes to $1/(1 - P)$
- ▶ It **doesn't matter how much compute** resource you throw at a problem, you can't reduce it further than this!


Distributed computation

- ▶ On a shared memory system, parallel computation is trivial:
 1. **Initialise** a parallelisable step, i.e.
 - ▶ enumerate the computations to be performed.
 2. **Assign** them to *worker threads*:
 - ▶ either evenly if compute resource is guaranteed and tasks take equal time, e.g. on a GPU,
 - ▶ or as a **queue**.
 3. **Action** the computation,
 4. **Block**, i.e. wait for all computations to complete.
- ▶ On completion, the results are in the same place in memory as if the computation was performed in series.

Accumulate/Reduce

- ▶ Suppose that you wanted to compute the cumulative sum. Then the elements become **dependent** and you cannot use a purely independent vectorization.
- ▶ How can we combine results from N parallel computations?
 - ▶ **accumulate** is a vectorisation of any (binary, i.e. pairwise) (associative and commutative) function returning a single value
 - ▶ It may or may not provide access to intermediate function evaluations
 - ▶ It is often called a **Reduce** operation
 - ▶ It is a natively parallelisable way to view combining

Accumulate/Reduce computation graph



- ▶ Computational graph properties:

- ▶ Nodes n internal to binary tree: $n(d) = \sum_{i=0}^d 2^i = 2^{d+1} - 1$
- ▶ Depth d : $d(n) = \Theta(\log(n))$

- ▶ Algorithm properties:

- ▶ Maximum compute could use $2^{d-1} = 2^{\log_2(n)} = n/2$ cores,
- ▶ Parallel maximum speedup: $\Theta(\log(n))$ due to depth,
- ▶ Simple blocking queue would reserve $n \log(n)/2$ processes,
- ▶ Parallel efficiency cost: $E = \Theta(n/(n \log(n)))$ if all memory operations are in place.

Map/Reduce parallel framework

- ▶ For general purpose computation, the concepts of **mapping** and **reducing** enable efficient parallel code.
 - ▶ This uses the concept of a **key-value** tuple.
- ▶ The data are **mapped**: each **value** is assigned one or more **keys**
- ▶ Data associated with each **key** is passed to a **reducer**
- ▶ The **reducer** completes the computation
- ▶ More precisely,
 - ▶ **Map**: $M(k_0, v_0) \rightarrow ((k_1, v_1), \dots, (k_K, v_K))$ is a function taking an input key/value pair to a list of output key/value pairs
 - ▶ **Reduce**: $R(k, (v_1, \dots, v_R)) \rightarrow (k, v)$ is a function taking an input key and list of values, to a single (list-valued) value.

Map/Reduce vector averaging example

- ▶ Let X be a vector of length N .
- ▶ **Map**: $(k_0, v) \rightarrow (k, \{w = 1, v = v\})$
 - ▶ Assign each element a **key** $k \in [1, \dots, K]$,
 - ▶ Assign a weight in the value,
 - ▶ The key acts as a **fold** of data.
 - ▶ Here, we are using the key as an arbitrary index, but this can be exploited.
- ▶ **Reduce**: $(k, \{v\}) \rightarrow (k, v)$
 - ▶ Count within each fold:
 - ▶ Return $(k, v) = (k, \{w = \sum_{k=1}^K v_w, v = \sum_{k=1}^K v_v\})$
- ▶ **Postprocess**: Return $\text{mean} = \frac{\sum_{k=1}^K v_{k,v}}{\sum_{k=1}^K v_{k,w}}$

Map/Reduce analysis

- ▶ Assume **within-memory** implementation
- ▶ Use $p \leq K$ parallel threads (assume an integer multiple for simplicity. . .)
- ▶ The **map** stage is entirely parallel for cost $\Theta(\lceil n/p \rceil)$
- ▶ There is a **sort** stage which would be handled by a set of K lists
 - ▶ Independently parallelised construction of the K lists for cost $\Theta(\lceil n/p \rceil)$
 - ▶ In memory concatenation cost is negligible
- ▶ The **reduce** stage is parallel across $\Theta(\lceil K \lceil n/K \rceil / p \rceil) \approx \Theta(\lceil n/p \rceil)$ processes
- ▶ The **postprocess** stage is naively sequential with compute cost K
 - ▶ Total parallel time: $T_p = \Theta(\lceil n/p \rceil + \lceil n/p \rceil + \lceil n/p \rceil + K)$
 - ▶ Total sequential time: $T_s = \Theta(n)$
 - ▶ Total efficiency loss: $T_p/T_s \sim \Theta(1 + Kp)$


Map/Reduce reducer parallelisation

► Practical concerns:


- Reducers don't automatically provide parallelism: we have to ask for it
 - This is because the reducer is not assumed to be commutative
 - But if the keys explicitly specify the desired folds, the reduce can be parallelised
 - In Hadoop/Spark Map/Reduce, reduction is parallelised **across keys**
 - In python/local Map/Reduce, reduction parallelisation is manual
- We can also **map** the **postprocess** k-fold reduction sum. Using p_2 processes:
- Reduce the postprocess time from K to $T'_p = \Theta(\lceil K/p_2 \rceil + \lceil K/p_2 \rceil + p_2)$
 - Minimized at $p_2 = \sqrt{K}$
 - So we should use $K = p^2$ keys, keeping $p_2 = p$.
 - Total parallel time: $T_p = \Theta(\lceil n/p \rceil + \lceil n/p \rceil + \lceil n/p \rceil + \sqrt{p})$

Map/Reduce Matrix Example

Elements required to compute (M, i, j)



Elements for which (M, i, j) is required



Map/Reduce Matrix Example

$$C = \begin{bmatrix} k & l \\ m & n \end{bmatrix} = AB = \begin{bmatrix} a & b & c \\ d & e & f \end{bmatrix} \begin{bmatrix} u & v \\ w & x \\ y & z \end{bmatrix}$$

- ▶ C has dimension $L \times L$, A has dimension $L \times K$
- ▶ where $k = au + bw + cy$, etc
- ▶ For a **one-stage** implementation, each of the **four** computations requires access to **three** elements from each array
- ▶ Represent the matrices in index form: $(key, value)$ where $key = (M, i, j)$ is the position (row and column) index and records the matrix type $M \in [A, B, C]$.
- ▶ Computing (C, i, j) requires all elements of A from row i and all elements of B from row j
- ▶ There will be $K = 3$ such elements
- ▶ Required to compute L^2 entries of C

Map/Reduce Matrix Multiplication Algorithm

- ▶ **Map**: each element is mapped independently to a list of K elements:
- ▶ $\text{Map}((M, i, j), v)$:
 - ▶ $((A, i, j), v) \rightarrow ((i, k), (A, j, v)) \quad \forall k = 1, \dots, K$
 - ▶ $((B, i, j), v) \rightarrow ((k, j), (B, i, v)) \quad \forall k = 1, \dots, K$
 - ▶ Cost: $2K$ for each of L^2 independent entries
- ▶ **Reduce**: each key (i, j) is received $2K$ times, K from A and K from B .
- ▶ $\text{Reduce}((i, j), (M, k, v))$:
 - ▶ $v_{i,j} = \sum_{k=1}^K v_{(A,k,v)} v_{(B,k,v)}$
 - ▶ Return $((i, j), v_{i,j})$
 - ▶ Cost: K for each of L^2 independent entries
- ▶ Cost:
 - ▶ Parallel time $T_p = \Theta(\lceil L^2/p \rceil K)$
 - ▶ Sequential time $T_s = \Theta(L^2 K)$
 - ▶ Efficiency 1
 - ▶ Despite inefficient duplication of data, which **fast** algorithms avoid!

Map/Reduce paradigm

- ▶ Map/Reduce is an essential tool in low-effort parallelism.
- ▶ The main computational advantage is that it is **scalable**: it can be parallelised across machines.
- ▶ So far we've described Map/Reduce as an **in memory** algorithm.
- ▶ In this case it naturally leads to fast analogues for a single computer:
 - ▶ We can imagine each **reducer key** being a memory location and the mappers are providing data fed to that location;
 - ▶ This is essentially how vectorised matrix computations are implemented efficiently.

Portfolio 09.2.P -

References

- ▶ Chapter 27 of Cormen et al 2010 **Introduction to Algorithms** covers some of these concepts.
- ▶ **Numpy vectorisation**
- ▶ **MapReduce algorithm for matrix multiplication**
- ▶ **Chrys Woods Parallel Python**
- ▶ See the non-taught **Block 12** content on Spark and HDFS if you want to learn about how this works on **Distributed data**.